

# 200TIG

## WELDING MACHINE FOR TUNGSTENS & ELECTRODES



### DC INVERTER HF TIG WELDER



**MULTIPURPOSE**  
TIG / MMA

**HF MODE**  
TIG by high frequency.

**DOWN SLOPE**  
Down slope time selection.

**POST FLOW**  
Post flow time selection.



**PROTECTION**  
Equipped with temperature, voltage and current sensor protection systems.

**VERSATILITY WITH GENERATORS**  
Developed to work with diesel generators and prepared to work even with the input voltage spikes.

**WEIGHT**  
Light and versatile equipment.

2T/4T TIG MODE

### PARAMETERS

Model	200TIG	Down Slope	0 - 10
Input Current (V)	1-220/230/240±10%	Net Weight	12lb (5.5kg)
Frecuency (Hz)	50/60	Dimensions (mm)	410x146x278
Rated Input Power (KW)	TIG 4.5 / MMA 7.0	Electrode Diameter	1.6 - 4.0
Rated Input Current (A)	TIG 32 / MMA 46	Electrode Types	6011, 7018, etc.
Duty Cycle (40°C 10min)	35%200A 60%125A 100%100A	Refrigeration	AF
No-load Voltage (V)	63	Insulation Class	H
Current Range (A)	10~200	Protection Class	IP23